



SA-60D-AS 1

School Digital Amplifier



**Your simple and cost effective
classroom solution.**

School Digital Amplifier SA-60D-AS 1

Model	SA-60D-AS 1
Power Source	220 – 240 V AC, 50/60 Hz
Rated Output	60 W
Power Consumption	100 W (rated output), 18 W (EN60065)
Frequency Response	20 Hz – 20 kHz
Distortion	1 % or less
Input	MIC 1, 2: -52 dB*, 600 Ω, unbalanced, ø6.3 phone jack (2P) AUX 1, 2: -20 dB*, 10 kΩ, unbalanced, RCA pin jack
Output	Speaker out: Low impedance (2 x 8 Ω or 1 x 4 Ω), Push-in terminal
Protection	Power Supply Thermal Shut down Power Amplifier Thermal Shut down Power Amplifier Over Current Each protection will be restored automatically
S/N Ratio	MIC 1, 2: 60 dB or more AUX 1, 2: 70 dB or more
Indicator	Power LED (Blue)
Operating Temperature	0 °C to +40 °C
Operating Humidity	90 %RH or less (no condensation)
Finish	Case: Steel plate, off-white, paint / Knob: ABS resin, black
Dimensions (W x H x D)	210 × 70.6 × 180 mm
Weight	1.6 kg
Accessory	Wall mounting pattern paper x 1

