2-Way Weatherproof Loudspeaker System

2-Way Weatherproof Loudspeaker System

ZS-760B-AS

ZS-760W-AS



- Highly intelligible ; suited to voice alarm, public address and BGM aplication by 2-way speaker system.
- IP 66 certified : All weather durability, be it water or dust.
- Ideal for any fully outdoor applications
- Special pain coat prevents color degradation, ensuring long-lasting exterior condition
- Rotary switch facilitates hassle-free impedance change

Specification	ZS-760B-AS	ZS-760W-AS
Rated Input	60W (high impedance)	
Rated Impedance	100V Line: 170Ω (60W), 330Ω (30W), 670Ω (15W), 1.3kΩ (7.5W) 70V Line: 83 Ω (60 W), 170 Ω (30 W), 330 Ω (15 W), 670 Ω (7.5W)	
Sensitivity (1W, 1m)	100dB	
Maximum SPL (60W,1m)	117dB	
Frequency Response	100Hz - 20kHz	
Crossover Frequency	2.5kHz	
Directivity Angle	Horizontal : 90° ; Vertical : 80°	
Speaker Component	Low Frequency : 16cm (6") cone-type High Frequency : 2.5cm (1") dome tweeter	
Dust/Water Protection	IP66	
Connection	Speaker cord (Hot: Black ; Corn: White)	
Finish	Enclosure: ABS, Black, Paint Coating Punched Net: Surface-treated Steel Plate, Black, Paint Coating Bracket: Stainless Steel, Black, Powder Coating	Enclosure: ABS, White, Paint Coating Punched Net: Surface-treated Steel Plate, White, Paint Coating Bracket: Stainless Steel, White, Powder Coating
Dimensions	388(W) x 310(H) x 367(D)mm	
Weight	7.4kg	

Subwoofer

Z-120BFB

Z-FB152B-AS





Specification	Z-120BFB	Z-FB152B-AS
Power Handling Capacity	Continuous pink noise: 200W, Continuous program: 600W	Continuous pink noise: 300W, Continuous program: 900W
Sound Pressure Level (1W/1m)	90dB	91dB
Rated Impedance	8Ω	
Frequency Response	40 - 1.200Hz (-10dB)	40-400Hz (-10dB)
Speaker Component	30cm cone-type	38cm cone-type
Input Connector	Speakon NL4MP x 2 and M4 screw terminal, distance between barriers:11mm	Speakon NL4MP x 2 and M4 screw terminal
Finish	Enclosure: Plywood. Punched Net: Steel plate, black paint	Enclosure: MDF, black or white, urethane paint. Punched Net: Surface-steel plate, black, paint
Dimensions	408(W) x 408(H) x 450(D)mm	505(W) x 530(H) x 655(D)mm
Weight	15kg	35kg