

YORK®

ITALY
POMPA AIR BERKUALITAS & TERPERCAYA

Pompa Celup Sumur Dalam

Submersible Deep Well Pump
3 SYK 1.8 - 2.5M³ (P)




MODEL	P ₂		DN	DELIVERY														
	KW	HP		n ≈ 2850 1/min														
1 ~ 160V - 240V				Q	m ³ /h	0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3.0	3.3	3.6
				l/min	0	5	10	15	20	25	30	35	40	45	50	55	60	
3 SYK 1.8 / 8 P	0.18	0.25	1"	H(m)	29	29	28	27	20	24	21	17	13	8				
3 SYK 2.5 / 11 P	0.37	0.5	1"		42	41	41	40	39	37	36	33	31	27	23	18	13	
3 SYK 2.5 / 16 P	0.55	0.75	1"		63	62	61	60	58	56	53	50	46	41	35	27	20	
3 SYK 2.5 / 21 P	0.75	1	1"		84	83	82	80	78	74	71	67	61	54	46	37	27	
3 SYK 2.5 / 31 P	1.1	1.5	1"		117	116	114	112	109	104	100	93	86	76	65	51	37	

SUBMERSIBLE DEEP WELL PUMP 3 SYK 1.8 / 2.5 (P)



Title



Fitur

1. Hemat Listrik
2. Semburan Deras
3. Voltage 160V - 240V
4. Bebas Perawatan
5. Tidak Berisik

Componen & Material

Components	Material
Pump external casing	AIISI 304 SS
Delivery casing	Cast-Cu ASTM C85500 AIISI 304 SS
Suction lantern	Cast-Cu ASTM C85500 AIISI 304 SS
Diffuser	Plastic PC
Impeller	Plastic POM
Shaft	AIISI 316 SS AIISI 304 SS
Shaft coupling	AIISI 316 SS AIISI 304 SS
Wear ring	AIISI 304 SS & Ceramic
Motor external casing	AIISI 304 SS
Top cover	Cast-Cu ASTM C85500
Bottom support	AIISI 304 SS
Mechanical seal	Special seal for deep well (Graphite-Ceramic TC)
Shaft	AIISI 303 SS-ASTM 1045 / 5140
Bearing	NSK
Seal lubricant oil	Oil for food machinery and pharmaceutical use.

Aplikasi

